

インパクトソケット寸法表

標準ソケット 差込角 88.9口

OZAT
2000 LTD.

QUALITY POWER TOOLS


3 1/2" SQUARE DRIVE



6 POINT IMPACT SOCKETS REGULAR LENGTH




六角対辺 A/F	UNネジ	CATALOG No.	D1	D2	L	t min	Weight
mm			mm	mm	mm	mm	gr
100	3 7/8"	5662	175	175	165	54.0	19200
	3 15/16"	5663M100	175	175	165	54.0	19200
	4"	5664	175	175	165	54.0	19200
	4 1/16"	5665	175	175	165	54.0	19200
105	4 1/8"	5666M105	175	175	165	54.0	19200
	4 3/16"	5667	175	175	174	62.0	19200
	4 1/4"	5668	175	175	174	62.0	19200
110	4 5/16"	5669M110	175	175	174	62.0	19200
	4 3/8"	5670	175	175	174	62.0	19200
	4 7/16"	5671	175	175	174	62.0	19200
	4 1/2"	5672	175	175	174	62.0	19200
115		56M115	175	175	174	62.0	19200
	4 5/8"	5674	175	175	182	67.0	20100
120		56M120	175	175	182	67.0	20100
	4 3/4"	5676	175	175	182	67.0	20100
	4 7/8"	5678	175	175	182	67.0	20100
125		56M125	175	175	182	67.0	20100
	5"	5680	190	175	190	72.0	22200
130	5 1/8"	5682M130	190	175	198	76.0	22200
	5 3/16"	5683	190	175	198	76.0	22200
	5 1/4"	5684	190	175	198	76.0	22200
135	5 5/16"	5685M135	190	175	198	76.0	22200
	5 3/8"	5686	200	175	198	76.0	23000
140	5 1/2"	5688M140	200	175	205	79.0	23000
	5 5/8"	5690	210	175	212	83.0	33100
145		56M145	210	175	212	83.0	33100
	5 3/4"	5692	210	175	212	83.0	33100
150	5 7/8"	5694M150	210	175	212	88.0	33100
	6"	5696	220	175	214	88.0	36000
155		56M155	220	175	214	88.0	36000
	6 1/8"	5698	220	175	214	88.0	36000
	6 1/4"	56100	220	175	218	91.0	36000
160		56M160	220	175	218	91.0	36000
	6 3/8"	56102	230	175	218	91.0	40000
165	6 1/2"	56104M165	230	175	230	94.0	40000
	6 5/8"	56106	240	175	230	94.0	46000
170		56M170	240	175	230	94.0	46000
	6 3/4"	56108	240	175	230	99.0	46000
175	6 7/8"	56110M175	250	175	230	99.0	52000
	7"	56112	250	175	237	104.0	52000
180		56M180	250	175	237	104.0	52000
	7 1/8"	56114	250	175	237	104.0	52000
185	7 1/4"	56116M185	260	175	237	104.0	59000
	7 3/8"	56118	260	175	242	107.0	59000
190		56M190	260	175	242	107.0	59000
	7 1/2"	56120	260	175	242	107.0	59000
195	7 5/8"	56122M195	270	175	246	109.0	62000
	7 3/4"	56124	270	175	249	112.0	62000
200	7 13/16"	56125M200	280	175	249	112.0	70000
	7 7/8"	56126	280	175	249	112.0	70000
	8"	56128	280	175	256	115.0	70000
	8 1/8"	56130	290	175	256	115.0	74000
210	8 1/4"	56132M210	290	175	256	115.0	74000
	8 3/8"	56134	290	175	263	120.0	74000
215		56M215	300	175	263	120.0	81000
	8 1/2"	56136	300	175	267	122.0	81000
	8 3/4"	56140	300	175	270	124.0	81000
225	8 7/8"	56142M225	310	175	273	126.0	90000
	9"	56144	310	175	276	128.0	90000
230		56M230	310	175	276	128.0	90000
	9 1/8"	56146	320	175	279	131.0	96000
235		56M235	320	175	279	131.0	96000
	9 1/4"	56148	320	175	285	133.0	96000
	10 1/4"	56164	340	175	330	145.0	128000



品質マネジメントシステム
ISO9001 準拠。
40年以上にわたり、OZATソケットは
高い品質と信頼性で世界60か国以上
で、認められ使用されています。

OZAT VS OTHER SOCKETS



オーザットのソケットは、ECM電気化学式に製造。ナットへの当たりが面タッチとなり、ナットを傷つけません。さらに六角の角が曲面仕上げで、丸みを持ち応力集中が無く、割れ難いソケットです。

株式会社 日本プララド

〒651-2404 兵庫県神戸市西区岩岡町古郷 255-6
TEL 078-967-3556 FAX 078-967-3567
<http://www.plarad.net/>